



Connects2Vision

User Manual

CAM-64

**Universal Wedge Mount Reverse Camera
with multiple LED's**

PRODUCT FEATURES:

Image Sensor: 1/3 CMOS

TV Lines: 600

Resolution: 756 x 504

Minimum Illumination: 0.1 Lux (0 when LED's are on)

TV System: NTSC

Waterproof Rating: IP68

Infra-red LED's: Yes (6)

Viewing Angle: 160 Degrees

Parking Lines: Yes (Removable)

Enhanced Performance In Low Light: Yes

Video Output: 1.0V p-p 75ohm

Operating Voltage 12V DC (Negative Ground)

Current Consumption: 50mA @ 13.8V

Operating Temperature: -20 Degrees C to +75 Degrees C

DISCLAIMER:

Prior to Installation

Read the manual prior to installation. Technical knowledge is necessary for installation. Please ensure you use the correct tools to avoid damage to the vehicle or product.

Connects2 can not be held responsible for the installation of this product.

Technical Support

Connects2 want to provide a fast and suitable resolution should you encounter any technical issues. With this in mind, when contacting Connects2, try to provide as much Information as possible. This will speed up the process and help us to help you.

Please use our dedicated online technical support centre: support.connects2.com

www.c2vision-eu.com

- Camera with wedge mount housing and cable to 4pin connector
- 2x Phillips screws
- 2x Self-tapping phillips screws
- 2x In-fill grommets
- Instructions

INSTALLATION

1. Select a suitable location for the camera and ensure that the area is free from all cables, fuel & oil. Whenever possible, avoid locations that are subject to road dirt & water spray.
2. Measure roughly where you want to place the camera, and cut a suitable hole using a cutting tool.
3. Thread the 4pin aviation connector into the hole and mount the camera in the desired position. Take the self-tapping screws from within the kit and drill this to the vehicle's body.
4. Proceed to wire the rest of the camera. Once done, place the in-fill grommets into the holes on either side of the camera.
5. Test the camera connection by turning on the ignition. The rear camera feed should now be visible on screen. Put the vehicle into reverse and the reverse camera feed will automatically populate on screen.
If camera feed is unresponsive, please uninstall the wiring and reinstall carefully in accordance with the above steps.
6. The camera will be default with parking guidelines. To remove this, simply cut the green wire found on the camera's connector.

**For further help and support, please contact us directly at
support.connects2.com/tickets/technical
and fill out a support ticket with the full details of your issue.**



Subscribe to our YouTube Channel for installation guides and tips... www.youtube.com/connects2