



Connects2Vision

User Manual

CAM-PE3

High Level Brake Light/Camera
Peugeot Boxer 2006 - 2018
Peugeot Manager 2007 - 2018

PRODUCT FEATURES:

Image Sensor: 1/4" Aptina – ASX340
TV Lines: 420
Resolution: 720 x 480
Minimum Illumination: 0 Lux
TV System: NTSC
Waterproof Rating: IP68
Viewing Angle: 170 (D) 140 (H) 85 (V) Degrees
Image: Mirror
Electronic Shutter: 30fps
Gamma Correction: 0.45
Enhanced Performance In Low Light: Yes
Video Output: 1.0V p-p 75ohm
Operating Voltage: 12V DC (Negative Ground)
Current Consumption: 43mA @ 13.8V
Operating Temperature: -30 Degrees C to +75 Degrees C

DISCLAIMER:

Prior to Installation

Read the manual prior to installation. Technical knowledge is necessary for installation. Please ensure you use the correct tools to avoid damage to the vehicle or product.

Connects2 can not be held responsible for the installation of this product.

Technical Support

Connects2 want to provide a fast and suitable resolution should you encounter any technical issues. With this in mind, when contacting Connects2, try to provide as much Information as possible. This will speed up the process and help us to help you.

Please use our dedicated online technical support centre: support.connects2.com

www.c2vision-eu.com

- Camera with 3m Cable to Male 2.5mm Connector
- 11m Camera Connection Cable with Female 2.5mm Connector to RCA Male Connector, Fused Power Wire and Ground Wire
- 2x Extension Bolts
- 1x Camera Adjusting Tool
- Instructions

INSTALLATION

1. Remove the third brake light from the vehicle and disconnect it.
2. Attach the 2x extension bolts to the nuts fixed to the vehicle which originally held the third brake light screws.
3. Insert the third brake light into the CAM-PE3, reconnect the power loom and refit to the vehicle taking care not to trap any cables.
4. Connect the camera to the camera connection cable.
5. Connect the Black wire to a suitable ground and connect the Red wire to the reversing light circuit or an interface which provides a reverse signal.
6. Connect the RCA Male connector to the display monitor and ensure that the image is displayed correctly.
7. If adjustment of the camera is needed, insert the adjusting tool into the 2 holes on the camera and move to the desired position.



Subscribe to our YouTube Channel for installation guides and tips... www.youtube.com/connects2