



Connects2Vision

User Manual

CAM-RT2.2

Renault Brake Light Reverse Camera
Renault Trafic (X82) 2014 >

PRODUCT FEATURES:

Image Sensor: 1/3" CMOS
Resolution: 510 x 492 (NTSC), 500 x 582 (PAL)
TV Lines: 700
Signal System: NTSC/PAL
Minimum Illumination: 0 Lux (LED's on)
Infra-Red LED's: Yes
Built-in Lens: f-2.8mm
Waterproof Rating: IP69K
Viewing Angle: 120° (Diagonal) x 95° (Horizontal) x 75° (Vertical)
Electronic Shutter: 1/60 (NTSC) 1/50 (PAL) - 1/100,00 second
Operating Voltage: 12V DC (Negative Ground)
Current Consumption: 69-117mA @ 13.8V
Operating Temperature: -30 Degrees C to +70 Degrees C
Certifications: FCC, CE, E-mark, ISO9001, TS16949, RoHs

DISCLAIMER:

Prior to Installation

Read the manual prior to installation. Technical knowledge is necessary for installation. Please ensure you use the correct tools to avoid damage to the vehicle or product.

Connects2 can not be held responsible for the installation of this product.

Technical Support

Connects2 want to provide a fast and suitable resolution should you encounter any technical issues. With this in mind, when contacting Connects2, try to provide as much Information as possible. This will speed up the process and help us to help you.

Please use our dedicated online technical support centre: support.connects2.com

- Camera with 65cm cable to Male 4pin camera connector
- 10m Male to Female 4pin extension cable
- Instructions

INSTALLATION

1. Remove the third brake light from the vehicle and unplug the connection cable.
2. Remove the bulb and refit it into the CAM-RT2.2
3. Connect the connection cable to the CAM-RT2.2 and refit to the vehicle taking care not to trap any cables.
4. Check for normal function of the third brake light.
5. Connect the camera cable to the 4pin extension cable.
6. Connect the Black wire to a suitable ground and connect the Red wire to the reversing light circuit or an interface which provides a reverse signal.
7. Connect the 4pin extension cable to the camera connection cable and connect the Yellow RCA connector to the display monitor using the supplied RCA splice and ensure that the image is displayed correctly.

PAL / NTSC SELECTION

To select PAL - leave the green wires separated



To Select NTSC - Connect the Green wires together



Subscribe to our YouTube Channel for installation guides and tips... www.youtube.com/connects2